



DONGGUAN JIUSHENG MACHINERY CO., LTD.

271, RENZHOU RD, DONGGUAN, GUANGDONG, CHINA

<http://www.dgchiller.com>; Email: cnjiusheng@dgchiller.com

WhatsApp: +86 158-1820-1390

FRP Cooling Tower Parameter

Model	Flow Rate (m³/h±5%)	Diameter (mm)	Height (mm)	Fan Diameter (mm)	Motor Power (KW)	Net Weight (kg±5%)	Operation Weight (kg±5%)	Noise db(A) ±5%
10T	7.8	945	1,530	600	0.18-6	46	190	62
15T	11.7	1,195	1,415	600	0.37-6	54	290	62.5
20T	15.6	1,195	1,590	730	0.55-6	67	300	63
30T	23.4	1400	1830	770	0.55	98	500	63
40T	31.2	1650	1705	770	0.55	130	550	63.5
50T	39.2	1,830	1,835	890	1.5-6	190	975	63.5
60T	46.8	2,145	1,955	1150	1.5 kW	240	1250	64
80T	62.4	2,145	2,035	1150	1.5 kW	260	1280	64.5
100T	78.1	2,900	2,370	1410	2.2 kW	500	1600	65.5
125T	97.5	2,900	2,555	1410	2.2kW	540	1640	66
150T	117	2,900	2,555	1410	2.2 kW	580	1680	66
175T	136.8	3,110	2,900	1750	4kW	860	1960	66
200T	156.2	3,110	2,900	1750	4kW	880	1980	66.5
250T	196.1	4120	3580	2050	4 (5.5)	1080	2800	68
300T	234	4730	3680	2350	5.5 (7.5)	1760	3930	68.5
350T	273.2	4730	3680	2350	5.5 (7.5)	1800	4790	68.5
400T	312.1	5600	3840	2745	11	2840	5740	68.5
500T	392.4	5600	3840	2745	11	2900	5800	69
600T	468	6600	4470	3400	15	3950	9350	70
700T	547.2	6600	4470	3400	18.5	4050	9450	70
800T	626.4	7600	4720	3700	22	4700	11900	73
1000T	781.2	7600	4720	3700	22	4900	12100	74